



L I S S E R S T O N E

THE ABILITY TO CUSTOMISE THE UPPER PANEL IN MATERIAL TO MATCH THE WORKTOP MEANS THE LISSER STONE IS THE ULTIMATE IN DISCREET EXTRACTION.

WIDTH	835MM OR 1135MM
DEPTH	98MM (WORKTOP), 195MM (BELOW WORKTOP)
HEIGHT	300MM FROM WORKTOP WHEN FULLY OPEN
FINISH	STAINLESS STEEL
CONTROLS	SEPERATE TOUCH CONTROL
LIGHTING	1X 5W LED (835 MODEL) 1X 9W LED (1135 MODEL)
FILTERS	CONCEALED ALUMINIUM MESH, SUITABLE FOR DISHWASHERS
DUCT POSITION	LEFT, RIGHT, FRONT, REAR OR DOWN
MOTOR OPTION	INTERNAL, REMOTE OR RECIRCULATING
ENERGY RATING (BOLT ON MOTOR)	A
ENERGY RATING (REMOTE MOTOR)	B
AIRFLOW RATING (BOLT ON MOTOR)	800 CMPH
MAXIMUM DB LEVEL (SPEED 4 - BOOST)	68DB (INTERNAL MOTOR)
POWER SUPPLY REQUIREMENT	3 AMP (INTERNAL) 5 AMP (REMOTE)
CUTOUT SIZE	100MM X 837MM (835MM VERSION) 100MM X 1137MM (1135MM VERSION)

