



STRATUS COMPACT

THE STRATUS COMPACT CAN ACCOMMODATE A REMOTE MOTOR WITH A HEIGHT OF ONLY 195MM. THIS UNIT EASILY FITS BETWEEN JOISTS WHETHER THEY RUN IN THE OPPOSITE DIRECTION TO THE PRODUCT OR THE POSITION IS UNKNOWN. THE COMPACT TOP BOX IS ROTATABLE ON SITE SO THE DUCT POSITION DOES NOT NEED TO BE SPECIFIED<

WIDTH	900MM OR 1200MM
DEPTH	440MM OR 600MM
HEIGHT	195MM (215MM RECIRCULATING)
FINISH	STAINLESS STEEL, WHITE PAINTED OR MIRROR POLISHED STAINLESS STEEL
CONTROLS	4 SPEED REMOTE CONTROL
LIGHTING	2 X 9W RAZOR X VARIABLE WARMTH 2400K - 6500K DIMMABLE LED LIGHT BLADES
FILTERS	CONCEALED ALUMINIUM MESH, SUITABLE FOR DISHWASHERS
DUCT POSITION	LEFT, RIGHT, FRONT OR REAR
MOTOR OPTIONS	INTERNAL, REMOTE OR RECIRCULATING
ENERGY RATING (INTERNAL MOTOR)	 B
ENERGY RATING (REMOTE MOTOR)	 B
AIRFLOW RATING (INTERNAL MOTOR)	800 CMFH
MAXIMUM DB LEVEL (SPEED 4 - BOOST)	72DB (INTERNAL MOTOR)
POWER SUPPLY REQUIREMENT	3 AMP (INTERNAL MOTOR) 5 AMP (REMOTE MOTOR)
CUSTOMISABLE OPTIONS	FINISH, LIGHTING, DIMENSIONS, POWER, CONTROLS
DUCT SIZE	150MM
CUTOUT SIZE	860MM/1160MM X 400MM/ 560MM

